

---

**Declaration of Performance (DoP) in acc. with**

**Construction Products (Amendment etc.) (EU EXIT) Regulations 2019 (No. 465)  
Construction Products (Amendment etc.) (EU EXIT) Regulations 2020 (No. 1359)**

**Nr. SZFG0921-UKCA-10025-28122022**

---

1. Unique identification code of the product type:

**Hot rolled constructional steel products**

2. Type, batch or serial number or any element allowing identification of the construction product:

**Continuously hot-rolled uncoated plate, sheet and strip made from non alloyed constructional steel S275M in acc. with EN 10025-4**

3. Intended use or uses of the construction product in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Welded, bolted and riveted structures**

4. Name, registered trade name or registered trademark and contact address of the manufacturer:

**Salzgitter Flachstahl GmbH  
Eisenhüttenstraße 99  
D-38239 Salzgitter, Germany  
+49 5341 21 - 01  
+49 5341 21 - 2727  
www.salzgitter-flachstahl.de**

5. Name and contact address of the authorised representative whose mandate covers the tasks:

**- not applicable -**

6. System or systems of assessment and verification of constancy of performance of the construction product:

**System 2+**

7. Declaration of performance concerning a construction product covered by a harmonised standard:

**Approved body - TÜV UK Ltd. (Reg.-Nr. 0879) - performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control in accordance with annex ZA of EN 10025-1:2004.**

**8. Declared performance:**

Essential characteristic	Performance								Harmonised technical specification
<b>Tolerances on dimensions and shape</b>	<i>thickness</i>		<i>see Page 3</i>						<b>EN 10025-1:2004</b>
	<i>width</i>								
	<i>length</i>								
<b>Yield strength</b>	<b>Nominal thickness (mm)</b> <i>t</i>		<b>Values</b> S275M - EN10025-4						
	>	≤	<b>R<sub>eH</sub> (MPa)</b>						
		16	≥						
	16	25	275						
<b>Tensile strength</b>		≤	<b>R<sub>m</sub> (MPa)</b>						
		25	≥			≤			
		25	370			530			
<b>Elongation</b>			<b>A<sub>5</sub> (%)</b>						
			≥						
	≤ 25		24						
<b>Impact energy</b>		≤	<b>KV (J)</b>						
		25	+20	0	-10	-20	-30	-40	-50
		25	≥						
<b>Weldability</b>		≤	<b>CEV (%)</b>						
		25				≤			
		25				0,34			
<b>Durability</b>		≤	<b>Ladle analysis (%)</b>						
		25				≥	≤		
		25	<b>C</b>						0,13
		25	<b>Si</b>						0,50
		25	<b>Mn</b>						1,50
		25	<b>P</b>						0,025
		25	<b>S</b>						0,025
		25	<b>Nb</b>						0,05
		25	<b>V</b>						0,08
		25	<b>Ti</b>						0,05
		25	<b>Cr</b>						0,30
		25	<b>Ni</b>						0,30
		25	<b>Mo</b>						0,10
	25	<b>Cu</b>						0,55	
	25	<b>N</b>						0,015	

<b>Tolerances on dimensions and shape</b>				
Thickness	Dimensions in mm			
Nominal thickness <i>t</i>	Tolerances for a nominal width			
	<i>w</i>			
	<i>w</i> ≤ 1200	1200 < <i>w</i> ≤ 1500	1500 < <i>w</i> ≤ 1800	<i>w</i> > 1800
<i>t</i> ≤ 2,00	± 0,17	± 0,19	± 0,21	-
2,00 < <i>t</i> ≤ 2,50	± 0,18	± 0,21	± 0,23	± 0,25
2,50 < <i>t</i> ≤ 3,00	± 0,20	± 0,22	± 0,24	± 0,26
3,00 < <i>t</i> ≤ 4,00	± 0,22	± 0,24	± 0,26	± 0,27
4,00 < <i>t</i> ≤ 5,00	± 0,24	± 0,26	± 0,28	± 0,29
5,00 < <i>t</i> ≤ 6,00	± 0,26	± 0,28	± 0,29	± 0,31
6,00 < <i>t</i> ≤ 8,00	± 0,29	± 0,30	± 0,31	± 0,35
8,00 < <i>t</i> ≤ 10,00	± 0,32	± 0,33	± 0,34	± 0,40
10,00 < <i>t</i> ≤ 12,50	± 0,35	± 0,36	± 0,37	± 0,43
12,50 < <i>t</i> ≤ 15,00	± 0,37	± 0,38	± 0,40	± 0,46
15,00 < <i>t</i> ≤ 25,00	± 0,40	± 0,42	± 0,45	± 0,50
Width	Dimensions in mm			
Nominal width <i>w</i>	Tolerances on width for sheet/plate			
	Mill edges		Trimmed edges	
	Lower value	Upper value	Lower value	Upper value
<i>w</i> ≤ 1200	0	+20	0	+3
1200 < <i>w</i> ≤ 1850	0	+20	0	+5
<i>w</i> > 1850	0	+25	0	+6
Length	Dimensions in mm			
Nominal length <i>l</i>	Tolerances on length for sheet/plate			
	Lower value		Upper value	
<i>l</i> < 2000	0		+10	
2000 ≤ <i>l</i> < 8000	0		+0,005 x <i>l</i>	
<i>l</i> ≥ 8000	0		+40	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for the manufacturer and on behalf of the manufacturer by:

Sven Schulz  
Manager Technical Customer Services

Salzgitter

28.12.2022

